

# DIGITAL CONFERENCE SYSTEM YC824



## YARMEE-YC824M conference centre control unit

The main unit can match the request no matter for few of representative delegate units in the small conference system, or the big conference system includes interpreter equipment, hundreds of representative units or wired and wireless language distribution equipments. The main unit has all the power supply for all of representative units and basic controlled function, and has port which connected with kind of other equipments. Also, it can reach much more function by adding other equipments and software.



## Features

- LCD display for status information and configuration
- Number control of the main unit and conference system single connecting and sounds signal adapted the same cable. (8DIN)
- Up to connect 240 pcs microphones with extension unit
- Operate independently or connect with computer external and use with software simultaneously, managing kinds of conference function (conference mode or operation: Appointed to speak, Free, Applied to speak and FIFO, etc)
- Single unit can manage functions: Open, Limit, FIFO
- 1~9 microphone speaker at the same time
- audio signal input interface, internal connects CD player or audio input equipment
- one group MIC input interface, external connects signal of handhold MIC and wireless MIC
- three group audio signal output interface, internal connects REC or audio equipment
- installed inside 19inch standard frame

## SPECIFICATIONS

Power Supply: 220V~240V -50Hz

Max Power Consumption:450W

Frequency response: 40-16kHz

Total harmonic distortion: < 0.1%

Dimensions: 500\*400\*13(mm)

Weight: 8.2kg

## YARMEE-YC824C/D Desktop Microphone unit

### Features

- Microphone on/off button
- Built-in high fidelity speaker and earphone jack.
- microphone gooseneck can be pull out
- 8-PIN T-type hand-in-hand interconnection cable
- Annular red indicator lamp could show the state of the microphone
- Chairman unit number in the system is unrestricted, can join in any position of the system.
- Chairman can turn down delegate MIC by priority button,
- C. only mode: only chairman microphone can be turn on

### SPECIFICATIONS

Frequency response: 50-16kHz

Sensitivity :42dB ± 2dB

Receiving distance: 15cm-50cm

Length of gooseneck 390mm

Size: 200\*120\*64(mm)

Weight:1kg



### Schematic diagram

