

YC834 Video+Built-in Speaker+Video



YC834M Main Controller

- Mix discussion, camera tracking and voting functions together.
- Teleconferencing is allowed with telephone coincidence.
- Built in frequency shifting, restraining screaming.
- The rack hole: fixed the main machine in the 19"standard rack.
- Holder Camera Setting: bring about the function of automatic tracking video.
- Tracking blackout remembering function, still tracking even breaking away from a computer.
- The main machine has 4 route can connect 80 units, through extend power machine can connect 2000 units.
- The computer and controlling the keyboard could bring about the function of automatic tracking video.
- It has LCD display screen menu of Chinese and English. Bring about the control of the meeting function with the function-key.
- Seceding computer, still having the following mode:
 - a: Free discussion model, turn on the unit or units (no limited) in arbitrary at the same times.
 - b: Amount limited model: turn on the unit with 1/2/3/4/5/6 at the same time.
 - c. FIFO model: speaking units 1/2/3/4/5/6 can be controlled.
 - d. Chairman mode: only allows the Chairman to speak
- The following mode must be set by computer software:
- Request: indicator light flicker after press ON button, software control switch.
Auto-meeting: Limit speaks time.

YC834M Main Controller

NAME	YC834M Main Machine
input/output	8P-DIN×4 XLRM×1 RCA×1 6.35mm×1
input	RCA×1
power supply	AC220V-50Hz
current drain	120W (MAX)
frequency response	100-14KHz
weight	8.5kg
(W、D、H) dimension	480×325×88mm
colors	Dark gray



YC834C/D Chairman/Delegate Unit

- Match with 2.1M connection cable.
- With two microphone input design (adding the lapel microphone hub)
- Inside work with DC24V power by Main machine, its safety for users.
- Loudspeaker with auto mute, earphone jack and volume adjusting knob.
- Chairman unit with priority speaking, can off each representative speaking unit.
- Chairman can shut down all delegates, and chairmen do not be limited by main machine.
- Unit-direction condenser microphone: goose neck microphone with red ring indicator LED.

- Open the microphone automatically mute speakers with headphone jack and volume control knob

YC834C/D SPECIFICATIONS

NAME	YC834C/D MIC UNIT
input/output	8P-DIN×1(2M)
input	Condenser Microphone
power supply	DC24V(Supplied by the host)
current drain	40mA
sensitivity	-47Db
s/n	65Db
frequency response	100-10KHZ
weight	1.1kg
(W、D、H) dimension	190×130×56mm
colors	Silver/Gray Black
installation	Desktop
MIC Stem Length	400mm (Activity)